

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE)
CB SCHEME

CB TEST CERTIFICATE

Product

POWER SUPPLY

Name and address of the applicant

SL POWER ELECTRONICS CORP
BLDG A
6050 KING DR
VENTURA, CA 93003 USA

Name and address of the manufacturer

SL POWER ELECTRONICS CORP
BLDG A
6050 KING DR
VENTURA, CA 93003 USA

Name and address of the factory

SL XIANGHE POWER ELECTRONICS CORP
NO.B-02-03,NORTH SIDE OF LANDSCAPE AVE, QIBU
DISTRICT, ENVIRONMENTAL INDUSTRIAL PARK XIANGHE
HEBEI 065400
CHINA

Note: When more than one factory, please report on page 2

 Additional Information on page 2

Ratings and principal characteristics

See Page 2

Trademark / Brand (if any)



Type of Customer's Testing Facility (CTF) Stage used

CTF Stage 3

Model / Type Ref.

NGB660SXXYZZ
See Page 2

Additional information (if necessary may also be reported on page 2)

 Additional Information on page 2

A sample of the product was tested and found to be in conformity with

IEC 62368-1:2014

As shown in the Test Report Ref. No. which forms part of this Certificate

E511363-A6012-CB-1 issued on 2020-11-24

This CB Test Certificate is issued by the National Certification Body



- UL (US), 333 Pfingsten Rd IL 60062, Northbrook, USA
- UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK
- UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN
- UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2020-11-25

Signature:

Jolanta M. Wroblewska



Ref. Certif. No.

US-37075-UL

Model Details:

NGB660SXXYZZ Where XX represents the output voltage which may be any number from 12 to 48. Y can be K (for Class I); ZZ can be any number between 00-99, blank or any letter from AA to ZZ, only for market purpose, not influence safety function.

Factories:

INDUSTRIAS S L S A DE C V
CIRCUITO SIGLO XXI 2055 COL PARQUE INDUSTRIAL EX-XXI 21254 MEXICALI BC
MEXICO

Ratings:

For convection,

Input: 100-110Vac, 50-60Hz, 8.0A; Output: 12-48Vdc, 27.55-8.20A, 5Vdc, 0.5A;

Input: 110-240Vac, 50-60Hz, 8.0A; Output: 12-48Vdc, 30.63-9.12A, 5Vdc, 0.5A;

For conduction,

Input: 100-110Vac, 50-60Hz, 8.0A; Output: 12-48Vdc, 35.05-9.70A, 5Vdc, 0.5A;

Input: 110-240Vac, 50-60Hz, 8.0A; Output: 12-48Vdc, 38.96-10.79A, 5Vdc, 0.5A;

For airflow 300LFM,

Input: 100-110Vac, 50-60Hz, 8.0A; Output: 12-48Vdc, 41.59-12.28A, 5Vdc, 1A;

Input: 110-240Vac, 50-60Hz, 8.0A; Output: 12-48Vdc, 46.25-13.65A, 5Vdc, 1A;

See Test Report for details.

Additional Information:

Additionally evaluated to EN 62368-1:2014/ A11:2017.

National differences specified in the CB Test Report.

Additional information (if necessary)



UL (US), 333 Pflingsten Rd IL 60062, Northbrook, USA

UL (Demko), Borupvang 5A DK-2750 Ballerup, DENMARK

UL (JP), Marunouchi Trust Tower Main Building 6F, 1-8-3 Marunouchi, Chiyoda-ku, Tokyo 100-0005, JAPAN

UL (CA), 7 Underwriters Road, Toronto, M1R 3B4 Ontario, CANADA

For full legal entity names see www.ul.com/ncbnames

Date: 2020-11-25

Signature:

Jolanta M. Wroblewska